

Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 11

SDS No.: 593423

V002.0 Revision: 03.04.2019

printing date: 17.08.2021

Replaces version from: 21.02.2017

UniBond 7E, all colours (2)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

UniBond 7E, all colours (2)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Joint sealant, silicone

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End

HP24RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000 Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information Contains N,N-Dimethyl-3-(trimethoxy sily l)propylamine. May produce an allergic

reaction.

Precautionary statement: P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

2.3. Other hazards

Evolves methanol during cure.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Joint sealants

Base substances of preparation:

Poly dimethy l siloxane

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Distillates (Petroleum) hydrotreated middle;	265-148-2	10- 20 %	Asp. Tox. 1
Gasoil - unspecified	01-2119552497-29		H304
64742-46-7	01-2119827000-58		
N,N-Dimethyl-3-	219-786-3	0,1-< 1 %	Eye Dam. 1
(trimethoxysilyl)propylamine	01-2120753783-46		H318
2530-86-1			Skin Sens. 1B
			H317

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hy giene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

${\bf 7.2.}\ Conditions\ for\ safe\ storage,\ including\ any\ incompatibilities$

Store in sealed original container.

Store in a cool, dry place.

Temperatures between 0 °C and + 30 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific enduse(s)

Joint sealant, silicone

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

In gre dient [Regulated substance]	ppm	mg/m ³	Value type	Shortterm exposure limit category/Remarks	Regulatory list
Silicon dioxide 112945-52-5		6	Time Weighted Average (TWA):		EH40 WEL
[SILICA, AMORPHOUS, INHALABLE DUST]					
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Methanol	250	333	Short Term Exposure		EH40 WEL
67-56-1	230	333	Limit (STEL):		EITTO WEE
[METHANOL]					
Methanol			Skin designation:	Can be absorbed through the	EH40 WEL
67-56-1				skin.	
[METHANOL]					
Methanol	200	266	Time Weighted Average		EH40 WEL
67-56-1			(TWA):		
[METHANOL]					
Methanol	200	260	Time Weighted Average	Indicative	ECTLV
67-56-1			(TWA):		
[METHANOL]	1				

Occupational Exposure Limits

Valid for

Ireland

In gre dient [Regulated substance]	ppm	mg/m ³	Value type	Shortterm exposure limit category / Remarks	Regulatorylist
Distillates (petroleum), hydrotreated middle 64742-46-7 [MINERAL OIL, PURE, HIGHLY & SEVERELY REFINED, INHALABLE FRACTION]		5	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Methanol 67-56-1 [METHANOL]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Methanol 67-56-1 [METHANOL]	200	260	Time Weighted Average (TWA):	Indicative	ECTLV

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction. If intensive ventilation/extraction is not possible then self-contained independent respiratory protection should be worn.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s). Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance paste

pasty

varied, according to

coloration

Odor neutral

Odour threshold No data available / Not applicable

No data available / Not applicable рΗ Melting point No data available / Not applicable No data available / Not applicable Solidification temperature Initial boiling point No data available / Not applicable No data available / Not applicable Flash point Evaporation rate No data available / Not applicable No data available / Not applicable Flammability Explosive limits No data available / Not applicable Vapour pressure No data available / Not applicable Relative vapour density: No data available / Not applicable

Density

0,99 g/cm3

(20 °C (68 °F))

Bulk density No data available / Not applicable Solubility No data available / Not applicable

Solubility (qualitative) Insoluble

(23 °C (73.4 °F); Solvent: Water)

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

Explosive properties

No data available / Not applicable
Oxidising properties

No data available / Not applicable
No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

Evolves methanol during cure.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (Petroleum) hydrotreated middle; Gasoil - unspecified 64742-46-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
N,N-Dimethyl-3- (trimethoxysilyl)propylam ine 2530-86-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
N,N-Dimethyl-3- (trimethoxysilyl)propylam ine 2530-86-1	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Distillates (Petroleum)	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
hydrotreated middle;				
Gasoil - unspecified				
64742-46-7				

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Distillates (Petroleum)	LC50	> 5,266 mg/l	dust/mist	4 h	rat	not specified
hydrotreated middle;						
Gasoil - unspecified						
64742-46-7						

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
N,N-Dimethyl-3-	not corrosive	4 h	Human,	OECD Guideline 431 (In Vitro Skin Corrosion:
(trimethoxysilyl)propylam			EpiSkinTM	Reconstructed Human Epidermis (RHE) Test Method)
ine			(SM),	
2530-86-1			Reconstructed	
			Human	
			Epidermis (RHE)	
N,N-Dimethyl-3-	not irritating	15 min	Human,	OECD Guideline 439 (In Vitro Skin Irritation:
(trimethoxysilyl)propylam	_		EpiSkinTM	Reconstructed Human Epidermis (RHE) Test Method)
ine			(SM),	-
2530-86-1			Reconstructed	
			Human	
			Epidermis (RHE)	

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
N,N-Dimethyl-3-	not irritating		Chicken, eye, in	OECD Guideline 438 (Isolated Chicken Eye Test Method)
(trimethoxysilyl)propylam			vitro test	
ine				
2530-86-1				

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
N,N-Dimethyl-3-	sensitising	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
(trimethoxysilyl)propylam		assay (LLNA)		Local Lymph Node Assay)
ine				
2530-86-1				

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
N,N-Dimethyl-3- (trimethoxysilyl)propylam	negative	bacterial reverse mutation assay (e.g	with and without		OECD Guideline 471 (Bacterial Reverse Mutation
ine 2530-86-1		Ames test)			Assay)

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

No data available.

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances	Viscosity (kinematic)	Temperature	Method	Remarks
CAS-No.	Value			
Distillates (Petroleum)	4 mm2/s	40 °C	not specified	
hydrotreated middle;			_	
Gasoil - unspecified				
64742-46-7				

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Distillates (Petroleum) hydrotreated middle; Gasoil - unspecified 64742-46-7	LC50	> 10.000 mg/l	96 h	1 1	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
N,N-Dimethyl-3-	EC50	> 100,1 mg/l	48 h	Daphnia magna	OECD Guideline 202
(trimethoxysilyl)propylamine					(Daphnia sp. Acute
2530-86-1					Immobilisation Test)

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
N,N-Dimethyl-3- (trimethoxysilyl)propylamine 2530-86-1	EC50	> 311 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N,N-Dimethyl-3- (trimethoxysilyl)propylamine 2530-86-1	NOEC	32,4 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

No data available.

12.2. Persistence and degradability

Hazardous substances	Result	Test type	Degradability		Method
CAS-No.				time	
Distillates (Petroleum)		aerobic	30 %	28 d	OECD Guideline 301 D (Ready
hydrotreated middle; Gasoil -					Biodegradability: Closed Bottle
unspecified					Test)
64742-46-7					•
N,N-Dimethyl-3-	not readily biodegradable.	aerobic	24 %	28 d	OECD Guideline 301 F (Ready
(trimethoxysilyl)propylamine					Biodegradability: Manometric
2530-86-1					Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
N,N-Dimethyl-3-	0,51	25 °C	QSAR (Quantitative Structure Activity Relationship)
(trimethoxysilyl)propylamine			
2530-86-1			

12.5. Results of PBT and vPvB assessment

Haz ardous substances	PBT/vPvB
CAS-No.	
Distillates (Petroleum) hydrotreated middle;	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
Gasoil - unspecified	Bioaccumulative (vPvB) criteria.
64742-46-7	
N,N-Dimethyl-3-(trimethoxysilyl)propylamine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2530-86-1	Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080410

SECTION 14: Transport information

14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture VOC content 0,00 %

VOC content (VOCV 814.018 VOC regulation CH)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.