

PVCu Solvent Cleaner

PROPERTIES

- ▶ Solvent-based, fast acting industrial grade cleaner
- ▶ High quality solvent with excellent cleaning properties
- ▶ Ideal for removing most contaminants
- ▶ Removes grime, excess grease, ingrained marks and uncured sealant without causing any damage to the plastic surface

APPLICATIONS

- Suitable for most types of white and veneered PVCu frames, sills, boards, panels and garden furniture
- recommended for PVCu window and door frames

PROCESSING

Application Method

Apply with a clean colourfast cloth, wipe away contamination and then polish with a clean dry cloth.

Storage

Store upright in cool dry conditions.

LIMITATIONS OF USE

It is the user's responsibility to determine suitability. A compatibility test is recommended on a hidden area of the surface prior to application.

CHARACTERISTICS

State	Liquid
Colour	Colourless
Odour	Perceptible odour
Solubility in H ₂ O	Highly soluble
Also soluble in	Acetone
Boiling point range	78.4°C to 115.4°C
Auto flammability	230
Relative density	0.791
Flammability limits	Lower: 3.3 % Upper: 19.0 %
Flash point	12 °C
Vapour pressure	5.8 kPa
pH	~ 7

Technical Datasheet
Version 09.09.2017
Pages 2



PACKAGING

UniBond Trade 132 is supplied in 1L bottles.

DISPOSAL

Product and packaging disposal

Dispose of waste and residues in accordance with local authority requirements (please refer to Safety Data Sheet for more information).

PVCu Solvent Cleaner

HEALTH & SAFETY



DANGER

Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking. Keep away from heat / sparks / open flames / hot surfaces – No Smoking. Avoid release into the environment. Wear protective gloves / protective clothing / eye protection / face protection.

IF ON SKIN (or Hair): Remove all contaminated clothing immediately. Rinse skin with water / shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

In case of fire: Use dry chemical powder, alcohol or polymer foam or carbon dioxide for extinction.

Safety Advice

Consult the Material Safety Data Sheet (mysds.henkel.com) for UniBond Trade 132.

www.unibond-trade.co.uk

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel AG & Co. KGaA

40191 Düsseldorf, Germany

Elch GmbH

Henkelstrasse 67 – D-40589 Düsseldorf

HPSA Ltd.

Hinckley, Leics. – LE10 1DP

Henkel Limited

Road 5, Winsford Industrial Estate, Winsford, Cheshire, CW7 3QY

www.unibond-trade.co.uk

